



BOSTON

Plug-in ice cream showcase.



Easy-to-use sales promotion.

The attractive ice cream showcase BOSTON is extremely comfortable to operate, and its illuminated glass dome attracts customers' attention. A plug-in storage and sales unit, BOSTON can be easily and flexibly repositioned.

Key benefits

- Optimal product visibility of merchandise for maximum sales attraction
- High energy savings compared with conventional open units
- Ecologically sound thanks to the natural refrigerant Propane
- 100 % CFC- and PFC-free
- Ready to plug in – no additional assembly required
- Intelligent fan motor for more energy efficiency – saves approximately 0,5 kWh daily
- Maintenance-free cooling technology



		BOSTON 210 (-)	
Technical Data		Scoping R290	Scoping
Gross content	litre	1340	1340
Net content according to EN 23953	litre	710	710
Total display area (TDA)	m ²	1,41	1,41
Classification according to EN 23953		3L1	3L1
Ambient temperature range	°C	+16 to +25	+16 to +25
Inner temperature range	°C	-12 to -23	-12 to -23
Sound pressure in 1 m distance	dB(A)	44	43,8
Electrical Data			
Nominal voltage/frequency	V/Hz	220-240/50	220-240/50
Nominal power cabinet	W	580	400
Nominal power illumination	W	50	50
Nominal current	A	4,0	2,6
Fuse protection	A	16	16
Energy consumption (at 25 °C)	kWh/24 h	5,1	5,7
Length of power supply cord	mm	1750	1750
Refrigeration Data			
Refrigerant type		R290	R404A
Refrigerant charge	g	110	250
Max. operating pressure	bar	30	30
Dimensions			
Length outside/inside	mm	2102/1970	2102/1970
Depth outside/inside	mm	854/720	854/720
Front access height/height outside	mm	757/1178	757/1178
Stacking height	mm	570	570
Weight			
Net weight (excl. packaging and internal accessories)	kg	161	162
Gross weight (incl. packaging, excl. internal accessories)	kg	180	181

